

# FREEDOM X SINE WAVE INVERTER

**xantrex™**  
Smart choice for power™



**Robust. Durable. Flexible.**

Available in:

1000W

2000W

3000W



The Freedom X inverter offers premium performance in a lightweight compact package. It cranks out **full output from -4°F - 104°F** for operation in all climate temperatures. The extended surge rating of the Freedom X makes it ideal to start difficult loads including fridge and microwave. The quick connect terminals at AC IN/OUT make installation a breeze.



Easy access AC & DC wiring compartment for quick installation



Hardwire or plug directly into the optional 20A GFCI receptacle



View AC & battery current, % status bar for inverter output on the onboard display

## Product Features

- » **Extended Surge Rating**  
Surges to 2X continuous power for 2 seconds for motor loads
- » **True Sine Wave AC Power**  
For operation of sensitive and motor loads
- » **Ignition Control**  
Feature to turn inverter on/off via a 12 VDC signal and to minimize battery drain by switching the inverter off when the ignition key is turned off
- » **Wide 10-18 VDC Input Range**  
Ensures inverter operation on high voltage alternators found on many new vehicle chassis
- » **Built-in 30A AC Transfer Relay**  
Senses when outside AC Power is present and transfers the load from the inverter to the source of incoming power (shore or generator)
- » **Quick Installation**  
Huge wiring bay for easy access and quick connect AC in/out terminals for fast & easy wiring

## Applications:



Recreational Vehicles



Heavy Duty Trucks



Work Vehicles



Specialty Vehicles



Marine



ETL listed to CSA Standard C22.2 No. 107.1 and UL 458\* with Marine supplement

\*For marine supplement compliance drip shield in specific mounting orientation is required. See installation guide



## Schneider Electric

3700 Gilmore Way  
Burnaby, British Columbia  
Canada V5A 4B5  
800 670 0707 Toll Free  
604 420 1591 Fax

541 Roske Drive, Suite A  
Elkhart, Indiana  
USA 46516  
800 446 6180 Toll Free  
574 294 5989 Fax

[WWW.XANTREX.COM](http://WWW.XANTREX.COM)

# FREEDOM X **SINE WAVE**

## INVERTER

**xantrex**<sup>™</sup>  
Smart choice for power<sup>™</sup>

Electrical Specifications	FREEDOM X1000	FREEDOM X2000
Operating Voltage Options	120, 110, 108 VAC	120, 110, 108 VAC
Continuous Power	Continuous Power 1000 W @40°C True sine wave	Continuous Power 2000 W @40°C True sine wave
Continuous Current	8.4 A	16.7 A
Surge Power	2000 W	4000 W
Frequency	60 (or 50) Hz	60 (or 50) Hz
Peak Efficiency	91%	91%
Full load Efficiency	≥ 87%	≥ 87.5%
Operating Voltage Range	85-140 VAC	85-140 VAC
Safe Non-Operating Voltage Range	Up to 240 VAC	Up to 240 VAC

General Specifications		
Operating Temperature Range	-4 to 140 °F (-20 to 60 °C), with output derated above 104 °F (40 °C)	-4 to 140 °F (-20 to 60 °C), with output derated above 104 °F (40 °C)
Storage Temperature Range	-40 to 158 °F (-40 to 70 °C)	-40 to 158 °F (-40 to 70 °C)
Humidity	5 to 95% RH, non-condensing	5 to 95% RH, non-condensing
Transfer Relay Rating	30A	30A
Operating voltage range	LBCO voltage - 18.0 VDC	LBCO voltage - 18.0 VDC
Maximum Non-Operating Voltage	24.0 VDC	24.0 VDC
Nominal Voltage (Inverting and Charging)	12.0 VDC	12.0 VDC
Nominal Current at Full Load	100 ADC	192 ADC
Part Number	817-1000	817-2000
L x W x H	14.2"(360mm) x 10.6"(270mm) x 3.7"(95mm)	15.4"(390mm) x 10.8"(275mm) x 4.0"(102mm)
Net Weight	13.4lbs (6.1kgs)	16.0lbs (7.3kgs)

Accessories		
Remote Panel (with 25' Cable)	808-0817-01	808-0817-01
GFCI Option	808-9817	808-9817
Remote Panel Cable	31-6257-00 (25 ft)	31-6257-00 (25 ft)
	31-6262-00 (50 ft)	31-6262-00 (50 ft)

Regulatory Approvals	
EMC and Safety	ETL listed to CSA 107.1 UL458 and UL458 Marine Supplement (drip shield with product number 808-1050 required) ABYC E11, A20, A25, A31

Actual product may differ slightly in appearance to images shown. Specifications subject to change.