

Absorbant Glass Mat (AGM) technology for superior performance. Valve regulated, spill proof construction allows safe operation in any position. Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified. U.L. recognized under file number MH 20567.

Maintenance-Free




Specification

Nominal Voltage	12 volts (6 cells)		
Nominal Capacity			
20-hr. (0.75A)	15.00 Ah		
10-hr. (1.40A)	13.95 Ah		
5-hr. (2.55A)	12.75 Ah		
1-hr. (9.00A)	9.00 Ah		
Approximate Weight	8.5 lbs. (3.85 kg)		
Shelf Life (% of normal capacity at 77° F (25° C))			
3 Months	6 Months	12 Months	
91%	82%	64%	
Temperature Dependency of Capacity (20 hour rate)			
104° F	77° F	32° F	5° F
102%	100%	85%	65%
AGM Operational Temperature			
Charge	0°C to 40°C		
Discharge	-15°C to 45°C		
AGM Storage Temperature	-15°C to 40°C		


Charge Method (Constant Voltage)		
Cycle Use (Repeating Use)		
Initial Current	4.5 A or smaller	
Control Voltage	14.6 - 14.8 V	
Float Use		
Control Voltage	13.6 - 13.8 V	

Physical Dimensions: in (mm)




L: 5.95in (151 mm)
W: 3.88in (98.5 mm)
H: 3.72in (94.5 mm)
TH: 3.94in (100 mm)
 Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

Terminals




Dimension Type	L	W	H	D	TP
F2	7.80	6.35	7.80	6.00	0.80


Discharge Time vs. Discharge Current




Discharge Characteristics




Battery Charging Characteristics for Standby Use




Battery Charging Characteristics for Cyclic Use




Shelf Life & Storage




Cycle Life vs Depth of Discharge



Open Circuit Voltage vs Residual Capacity



Effect of Temperature on Capacity



Charge Current & Final Discharge Voltage

Application	Charge Voltage(V/Cell)			Max.Charge Current	Final Discharge Voltage V/Cell	1.75	1.70	1.60	1.30
	Temperature	Set Point	Allowable Range						
Cycle Use	25°C(77°F)	2.45	2.43-2.47	0.30C	Discharge	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C
Standby	25°C(77°F)	2.28	2.27-2.30		Current(A)				



Let UPG Power Your Life.

www.upgi.com