



## DC-AC Inverter Pure Sine Wave

Model  
NTX-600-12  
12 VDC - 115 VAC  
NTX-600-24  
24 VDC - 115 VAC

### Design Features

- Compact and lightweight
- Rugged and reliable, easy to use
- High surge: 2X continuous power with soft start
- True sine wave power ideal for all loads
- Cool Surface technology
- USB 2.1A charging port
- Protections: thermal, battery low/high, overload, short circuit & ground fault
- Battery clamps included

2 YEAR LIMITED WARRANTY  

	MODEL NO.	NTX-600-12	NTX-600-24
INPUT	DC INPUT VOLTAGE RANGE	10.5 - 16.3 VDC (± 0.3 VDC)	21.0 - 32.6 VDC (± 0.5 VDC)
	DC INPUT CURRENT AT RATED LOAD	60 A	30 A
	DC INPUT CURRENT AT NO LOAD	< 0.9 A	< 0.5 A
OUTPUT	AC OUTPUT VOLTAGE	115 VAC (± 5 VAC)	
	AC OUTPUT FREQUENCY	60 Hz (± 1 Hz)	
	AC OUTPUT WAVE FORM	Pure Sine Wave	
	CONTINUOUS ACTIVE OUTPUT POWER	600 W	
	MAXIMUM ACTIVE SURGE POWER (LESS THAN 1 SEC)	1200 W	
	PEAK EFFICIENCY	91%	
USB PORTS	OUTPUT	5 VDC, 2.1 A Maximum, Type A	
PROTECTIONS	LOW INPUT VOLTAGE WARNING ALARM	11.0 VDC ± 0.3 VDC	22.0 VDC ± 0.5 VDC
	LOW INPUT VOLTAGE SHUTDOWN	10.5 VDC ± 0.3 VDC	21.0 VDC ± 0.5 VDC
	HIGH INPUT VOLTAGE SHUTDOWN	16.3 VDC ± 0.3 VDC	32.0 VDC ± 0.5 VDC
	OVERLOAD/SHORT CIRCUIT SHUTDOWN	Yes. Manual reset	
	OVER TEMPERATURE SHUTDOWN	Yes. Auto reset	
	COOLING	Load and temperature controlled variable speed fan	
CONNECTIONS	INTERNAL FUSES	3 x 30 A in parallel	2 x 25 A in parallel (Automotive Blade Fuses, Type ATO/ATC, 32 VDC)
	INPUT	Thumb Screw M4 Terminals - Requires Custom Rectangular Lug: (Use Provided DC Cable)	
	OUTPUT	2x NEMA5-15R Receptacles	
COMPLIANCE	SAFETY	Intertek - ETL Listed. Conforms to UL Std. 458 and certified to CSA Std. C22.2 No. 107.1	
	EMI/ EMC	FCC Part 15(B), Class A	
GENERAL	OPERATING AMBIENT TEMPERATURE	-25 °C to 50 °C / -13 °F to 122 °F	
	STORAGE TEMPERATURE	-30° C to 70 °C; -22° F to 158 °F	
	DIMENSIONS (W x D x H), INCHES	6.10 x 10.0 x 2.32	
	DIMENSIONS (W x D x H), MM	155 x 254 x 59	
	WEIGHT, KG	1.1	
	WEIGHT, LB	2.4	

- NOTES:
1. All power ratings are specified for resistive load at Power Factor = 1
  2. All specifications given above are at ambient temperature of 25°C / 77°F
  3. Specifications are subject to change without notice

12002-NTX-600-12-24-0825