



Inverter Remote Control

Pure Sine Wave

Model
S-R8

Design Features

- Designed for use with 12V / 24V / 48V versions of SA, SK & ST Series of Pure Sine Wave Inverters
- Push button system ON/OFF
- LED indicators for ON conditions, remote override and ignition lockout
- 10 feet of connecting cable included

2 YEAR WARRANTY

| | | | |
|--|--|--------|---------|
| MODEL NO. | S-R8 | | |
| INPUT VOLTAGE | 12V or 24V or 48V Nominal Battery System Voltage | | |
| STANDBY CURRENT DRAW | < 40 mA | | |
| OPERATING TEMPERATURE RANGE | 0°C to 40°C / 32°F to 104°F | | |
| STORAGE TEMPERATURE RANGE) | -30°C to 70°C / -22°F to 158°F | | |
| CONNECTING CABLE | <ul style="list-style-type: none"> - 10 ft, 4 Conductors - 4P4C or 6P4C Modular Plugs - Straight Connection | | |
| DIMENSIONS, INCHES (W x D x H) | 2.3 x 1.1 x 2.9 | | |
| DIMENSIONS, MM (W x D x H) | 57 x 28 x 74 | | |
| WEIGHT (WITHOUT CABLE), g | 32 | | |
| WEIGHT (WITHOUT CABLE), lbs | 0.07 | | |
| FOR USE WITH SPECIFIC INVERTER MODELS | SA-1000K | SK700 | ST-1500 |
| | SA-2000K | SK1000 | |
| | SA-3000K | SK1500 | |
| | | SK2000 | |
| | | SK3000 | |